



Innenschicht: Thermoplastik Polymer
 Drucklagen: zwei hochzugfeste synthetische Textileinlagen
 Aussenschicht: Polyurethan - abriebfest, witterungsbeständig
 Anwendung: für Hochdruckanwendungen mit Wasser und Kanalreinigung

200 bar

ID			OD	WP		BP		BR	W
DN	mm	inch	mm	bar	Psi	bar	psi	mm	g/m
12	13,0	1/2"	22,4	200	2900	500	7250	75	277
16	16,0	5/8"	26,5	200	2900	500	7250	100	372
20	19,2	3/4"	29,8	200	2900	500	7250	120	431
25	25,6	1"	37,3	200	2900	500	7250	150	580
32	32,0	1 1/4"	46,0	200	2900	500	7250	235	848

250 bar

ID			OD	WP		BP		BR	W
DN	mm	inch	mm	bar	Psi	bar	psi	mm	g/m
20	19,2	3/4"	29,8	250	3625	625	9060	120	460
25	25,6	1"	37,3	250	3625	625	9060	150	643
32	32,0	1 1/4"	46,0	250	3625	625	9060	235	985



-40°C / +55°C / -40°F / +131°F

Spezifikationen

Betriebsdruck Sicherheitsfaktor: 1:2,5